
ASKARI Panel & Flange

Specification


Operating Voltage	18-24V AC
Operating Current	17-41mA
Current Consumption Nom	See Tones Table Below
Operating Temperature	-25°c - +70°c
Case Material	ABS
Environment Category	Type A/B
Ingress Protection	IP65

Connection Details




Dimensions

Askari Panel




6 Way Switch Variants

Example of Tone 3 setting



5 Way Switch Variants

Example of Tone 3 setting



Tones table

Primary tone	Secondary tone	Switch setting	Tone Description				Main Application	Askari			
								18Vac		24Vac	
		12345	Pattern	Frequency Hz	Rate	Description		SPL(db(A))	I(mA)	SPL(db(A))	I(mA)
1	14	11111	Alternating	800 & 970	2Hz (250ms-250ms)		BS Fire tone	95	18	97	23
2	14	11110	Sweep	800 to 970	7Hz (7/s)		BS Fire tone	97	18	99	23
3	14	11101	Sweep	800 to 970	1Hz (1/s)		BS Fire tone	98	19	100	23
4	14	11100	Continuous	2850	Steady			93	30	95	37
5	4	11011	Sweep	2400 to 2850	7Hz			100	32	103	41
6	4	11010	Sweep	2400 to 2850	1Hz			101	32	103	41
7	14	11001	Slow whoop	300 to 1200	3s sweep, 0.5 s silence, then repeat		Dutch Fire tone	100	21	101	25
8	14	11000	Sweep	1200 to 500	1Hz		Din tone	100	23	102	29
9	4	10111	Alternating	2400 & 2850	2Hz (250ms-250ms)			98	31	100	40
10	14	10110	Intermittent	970	0.5Hz (1s On/1s Off)			97	18	99	23
11	14	10101	Alternating	800 & 970	1Hz (500ms-500ms)		BS Fire tone	96	18	98	23
12	4	10100	Intermittent	2850	0.5Hz (1s On/1s Off)			95	28	96	36
13	14	10011	Intermittent	970	0.8Hz (250ms On/1s Off)			95	10	96	12
14	14	10010	Continuous	970	Steady		BS Fire tone	97	19	99	24
15	14	10001	Alternating	554 & 440	100ms-400ms		French fire tone	99	22	101	28
16	16	10000	Intermittent	660	3.3Hz (150ms On/150msOff)		Swedish fire tone	96	14	98	17
17	17	01111	Intermittent	660	0.28Hz(1.8s On/1.8s Off)		Swedish fire tone	92	16	94	20
18	18	01110	Intermittent	660	0.05Hz (13s Off / 6.5Hz On)		Swedish fire tone	92	17	94	20
19	19	01101	Continuous	660	Steady		Swedish fire tone	92	16	94	20
20	20	01100	Alternating	554 & 440	0.5Hz (1s On/1s Off)		Swedish fire tone	94	23	96	29
21	21	01011	Intermittent	660	1Hz (500ms-500ms)		Swedish fire tone	92	11	94	19
22	14	01010	Intermittent	2850	4Hz (150ms On/100ms Off)		Pelican crossing	91	24	93	31
23	14	01001	Sweep	800 to 970	50Hz		BS Fire tone	92	18	94	23
24	4	01000	Sweep	2400 to 2850	50Hz			96	32	98	41
25	25	00111	Intermittent	970	3 x 500ms pulses followed by 1.5s silence then repeat		ISO 8201	92	17	94	22
26	26	00110	Intermittent	800 & 970	3 x 500ms pulses followed by 1.5s silence then repeat		ISO 8201	93	10	95	20
27	27	00101	Alternating	970 & 800	2Tx3 1.5s silence then repeat			92	17	94	22
28	10	00100	Alternating	800 & 970	2Hz (250ms-250ms)		BS Fire tone	92	18	94	23
29	33	00011	Alternating	990 & 650	2Hz (250ms-250ms) (Symphoni tones)		BS Fire tone	95	33	93	26
30	35	00010	Alternating	510 & 610	2Hz (250ms-250ms) (Squashni Micro tones)		BS Fire tone	93	26	95	34
31	31	00001	Sweep	300 to 1200	1Hz			94	25	96	30
32	32	00000	Alternating	510 & 610	Steady			94	22	95	

Cooper Fulleon Ltd, Cwmbran, South Wales, UK
See Fulleon Web Site : www.cooperfulleon.com